

CBD20-410 2.0 Ton Electric Pallet Truck

Advantages

- Mechanical Steering-Economic, comfortable, more reliable.
- AC Driving System-Low noise, quiet, without carbon brush and free maintenance.
- © Electric Lifting-Rapid, efficient, electricity limit switch is Standard.
- Excellent Design-Easily in and out of the double tray.
- © Energy conservation-Save energy, more environmentally friendly.
- O AC Controller-Stepless, strong power, multiple automatic protection.



AC | Electronic limiter

Fork suitable for reversible pallet



TOP1 FORKLIFT MANUFACTURER AND SALER IN CHINA FOR CONSECUTIVE 24 YEARS

HELI CBD20-410

Feature	17	
Model		CBD20
Configuration No.		410
Loading capacity	kg	2000
Load center	mm	600
Wheel base	mm	1407
Operating type		Pedestrian / Ride On
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Driving wheel size	mm	⊄248×75
Bearing wheel size	mm	Ø84×80(Double wheels)
Balance wheel size	mm	€115×55
Dimension	*	
Min.fork lowered height	mm	85
Max.fork lifting height	mm	195
Max.lifting height	mm	110
Overall fork width	mm	550/600/650/685
Inside width between forks	mm	210/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1874/2247
Overall width	mm	725
Overall height(With handle)	mm	1475
Overall height(Without handle)	mm	940
Min.Turning radius	mm	1680/2060
Min.Aisle width for pallets 800×1200	mm	2000/2320
Min.Aisle width for pallets 1000×1200	mm	2030/2340
Performance		
Travel speed, laden/unladed	km/h	5.5/6.0
Lift speed,laden/unladed	mm/s	20/25
Lowering speed,laden/unladed	mm/s	40/30
Gradeability,laden/unladed	%	5/7
Electrical configuration		
Drive motor	kW	AC 1.5
Lift motor	kW	DC 1.2
Steering motor	kW	-
Battery voltage / capacity	V/Ah	24/210
Brake	or associated first	Electromagnetic/Regenerative
Controller		CURTIS
Weight	<u> </u>	
Battery weight	kg	202
Service weight with battery	kg	710
	- 9	/10

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA

TEL: +8655163639068 FAX: +8655163639966

Email: heli@helichina.net WEBSITE: WWW.HELICHINA.COM/WWW.HELICHINA.NET

© 2015 heli copyright

Catalog No.2015.04 HELI Print