

HELI
LIFTING THE FUTURE

CBD20/25/28/30

Electric Ride-on Pallet Truck

Popular



Advantages

Configuration and Performance

- ⊙ Electronic power steering system, light and low noise.
- ⊙ Drive unit floating bodies with patent design.
- ⊙ AC Driving system, No carbon brush, maintenance free.
- ⊙ USA CURTIS driving controller.
- ⊙ Electromagnetic, regenerative braking system.
- ⊙ Automatic lifting limit, extend the life of the battery and motor.
- ⊙ Side-way battery, easy to replace.

Safety

- ⊙ Curve automatic deceleration devices, more safe.
- ⊙ Stepless speed control system, safe and quiet.
- ⊙ Controller with Multiple automatic protection.
- ⊙ Emergency reversing device/Emergency brake switch.

Side-loaded battery EPS/AC

Steering automatic deceleration



TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

HELI CBD20/25/28/30-460

Feature		
Model		CBD20/25/28/30
Configuration No.		460
Loading capacity	kg	2000/2500/2800/3000
Load center	mm	600
Wheel base	mm	1493
Operating type		Ride On
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/2/4
Driving wheel size	mm	∅248×75
Bearing wheel size	mm	∅84×80(Double wheels)
Balance wheel size	mm	∅115×55
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	550/600/650/685
Inside width between forks	mm	210/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1916/2333
Overall width	mm	790
Overall height(With handle)	mm	1455
Overall height(Without handle)	mm	845
Min.Turning radius	mm	1746/2158
Min.Aisle width for pallets 800×1200	mm	2046/2435
Min.Aisle width for pallets 1000×1200	mm	2077/2458
Performance		
Travel speed,laden/unladed	km/h	6/6
Lift speed,laden/unladed	mm/s	56/60
Lowering speed,laden/unladed	mm/s	57/59
Gradeability,laden/unladed	%	5/7
Electrical configuration		
Drive motor	kW	AC 1.5
Lift motor	kW	DC 1.2
Steering motor	kW	DC 0.15
Battery voltage / capacity	V/Ah	24/270
Brake		Electromagnetic/Regenerative
Controller		CURTIS
Weight		
Battery weight	kg	245
Service weight with battery	kg	840

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA
TEL: +8655163639068
FAX: +8655163639966
Email: heli@helichina.net
WEBSITE: WWW.HELICHINA.COM / WWW.HELICHINA.NET

© 2015 heli copyright

Catalog No.2015.04 HELI Print